

Features

Liquid Coffee Chilled Dispenser

- Attractive appearance and narrow (12") width.
- Dispense over 125 - 5 oz. cups per hour with a 120 volt, 15 amp electrical connection or over 500 - 5 oz. cups per hour with a 240v/30a electrical connection.
- Accommodates all ½ gallon and most 1 gallon bag-in-box (BIB) containers.
- Chilled product cabinet extends product flavor profile.
- Refill or rinse LED lights alert the operator when more concentrate or cleaning is needed.
- Global multi-volt design is easily converted to ratings from 100 to 240 volts (50-60 hertz) eliminating the need to inventory multiple electrical configurations.
- FlavorGard™ technology continuously monitors extract-to-water ratio and assures flavor consistency.
- Set up for continuous draw (by the cup) for self-serve applications or portion-control to fill carafes or decanters.
- Sanitation listed by ETL to NSF Standard 18 and safety listed by ETL to UL Standard (UL 197) and CSA Standard (C22.2 No. 109 - model LCC-2C)



LCC-2

Dimensions: 35.8" H x 12.2" W x 24.9" D

Related Products

For current specification sheets and other information, go to www.bunnomatic.com.

BUNN recommends the use of our Easy Clear® Water Quality Systems to assure perfect taste.

Easy Clear® EQ-11-TL

Product No. : 30344.1001

Dimensions: 15⁷/₈" H x 3³/₈" W x 4¹⁷/₃₂" D

Use with 1.8 oz./sec. flow rate.



Easy Clear® EQ-21-TL, TL

Product No. : 30325.1000

Product No. : 30331.1001 (x2)

Use with 2.5 oz./sec. flow rate.



1/8" Replacement tube kits

Product No. : 34728.1000



3/16" Replacement tube kits

Product No. : 34727.1000



50ml Graduated Cylinder Kit

Product No. : 34843.1000

For use in calibration of pumps.



Scholle BIB connector

Product No. : 35057.0000

LiquiBox QC/D II BIB connector

Product No. : 35055.0000



BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

ITEM#

PROJECT

DATE

International
Model

LCC-2A

Model

LCC-2

BUNN®

Corporate Offices

1400 Stevenson Drive
Springfield, Illinois 62703

Phone

800-637-8606
217-529-6601

Fax

217-529-6644

Technical Services

800-286-6070

Internet

<http://www.bunnomatic.com>

Western Regional Office

16431 Carmenita Road,
Cerritos, California 90701

Phone

562-926-0764

Fax

562-926-0858

Canadian Office

280 Industrial Parkway South
Aurora, Ontario, L4G 3T9

Phone

905-841-2866

Fax

905-841-2775

Patents
Apply



Dimensions & Specifications

Model	Product Number	Dispense Rate/Sec.		Connector Type	Volts	Amps	Heater Watts	Capacity**	Cubic Feet	Shipping Weight	Cord Attached
		1.8 oz.	2.5 oz.*								
LCC-2	34400.0005 [†]	45:1-100:1	65:1-100:1	Scholle 1910LX	120	15	1500	125 cups/hr.	9.3	85 lbs. (38.6 kg)	Yes
LCC-2	34400.0006 [†]	25:1-45:1	25:1-65:1	Scholle 1910LX	120	15	1500	125 cups/hr.	9.3	85 lbs. (38.6 kg)	Yes
LCC-2	34400.0007 [†]	45:1-100:1	65:1-100:1	LiquiBox QC/D II	120	15	1500	125 cups/hr.	9.3	85 lbs. (38.6 kg)	Yes
LCC-2	34400.0008 [†]	25:1-45:1	25:1-65:1	LiquiBox QC/D II	120	15	1500	125 cups/hr.	9.3	85 lbs. (38.6 kg)	Yes
					208	30	4500	385 cups/hr.	9.3	85 lbs. (38.6 kg)	No
					240	30	6000	512 cups/hr.	9.3	85 lbs. (38.6 kg)	No

[†] All models can be changed to these electrical configurations.

*Unit shipped with dispense rate set at 1.8 Oz./sec. Dispense rate increases to 2.5 Oz./sec. if restrictor plug is removed.

**Capacity measured with a 5 oz. cup.

Electrical: 120V model requires 2-wires plus ground service rated 120V, single phase, 60 hz.

Plumbing: 20-90 psi (138-621 kPa) from a 3/8" (10 mm) or larger supply line. Unit requires a 2.2 gpm line flow capacity. A shut-off valve should be installed in the line before the unit. Install a regulator in line when pressure is greater than 90 psi to reduce pressure to 50 psi. Supplied with 3/8" (10 mm) male flare fitting.

